



1999 GMC Sierra Radio Replacement Radio Replacement

Replacing a radio in a 1999 GMC Sierra SLE. Based off replacing a stock radio with a XO Vision XD107BT radio.

Written By: Blake Moss



INTRODUCTION

This guide will show the steps of replacing a radio in a 1999 GMC Sierra SLE. The radio that is being replaced is a stock radio, and the new radio is a XO Vision XD107BT.

Since you'll be handling electrical cords during this installation, we recommend unplugging the car battery before proceeding with the replacement.



PARTS:

- [XO Vision XD107BT Radio](#) (1)
-

Step 1 — Radio



- Use the gear shift to shift the truck from 'Park' to '1st Gear' so that the dash face is easily accessible.
- Pop the dash face off, and place it to the side until the radio has been replaced

Step 2



- Remove the radio from its place.
- Remove the bundled cable connector from the back of the radio unit.
- Remove the antenna plug from the back of the radio unit.

Step 3



- Attach the radio plug to the back of the new radio.
- Also, attach the antenna chord to the back of the new radio.

Step 4



- Align the slots along the sides of the new radio with the ones in the dash.
- Push new radio in until you hear a 'pop' sound, telling you the new radio is in place.
- Press the power button on new radio to insure that it works properly.

Step 5



- Replace dash face! Then you are finished!

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-07-20 11:54:53 AM.